

# UP55N-VR

55 mm Ø, 15 mW - 200 W, Volume Absorber




## KEY FEATURES

- 1 Modular Concept**  
 Increase the power capability of your detector:  
 4 different cooling modules
- 2 High Peak Power Volume Absorber**
  - Perfect for high density beams
  - Average power density of 700 W/cm<sup>2</sup> prevents degradation caused by repetitive pulses
- 3 Large Aperture**  
 55 mm Ø aperture accomodates the largest beams
- 4 High Average Power**  
 Up to 200 W of continuous power with the water-cooled unit
- 5 Energy Mode**  
 Measure single shot energy up to 200 J
- 6 Smart Interface**  
 Containing all the calibration data


## AVAILABLE MODELS




UP55N-50S-VR  
(50W-Standalone)



UP55N-100H-VR  
(100W-Heatsink)



UP55N-150F-VR  
(150W-Fan-Cooled)



UP55M-200W-VR  
(200W-Water-Cooled)

## ACCESSORIES



Stand with Steel Post  
(Model Number: 200234)



Extension Cables  
(4, 15, 20 or 25 m)



Fiber Adaptors and Connectors  
(FC, SC or SMA)



3-Port Fiber Cylinder with  
Adaptors and Plug



12V Power Supply  
(Model Number: 200130)



Pelican Carrying Case

## SEE ALSO

HOW IT WORKS	12
CALIBRATION	6
TECHNICAL DRAWINGS	88
COMPATIBLE MONITORS	
MAESTRO	18
TUNER	22
UNO	24
S-LINK-2	26
P-LINK	28
M-LINK	30
LIST OF ALL ACCESSORIES	174

# UP55N-VR

## SPECIFICATIONS



\*Also traceable to NRC-CNRC

MODELS	UP55N-50S-VR	UP55N-100H-VR	UP55N-150F-VR	UP55M-200W-VR
<b>MAX AVERAGE POWER (CONTINUOUS / 1 MINUTE)</b>	50 W / 50 W	100 W / 100 W	150 W / 150 W	200 W <sup>g</sup> / 200 W <sup>g</sup>
<b>EFFECTIVE APERTURE</b>	55 mm Ø	55 mm Ø	55 mm Ø	55 mm Ø
<b>COOLING METHOD</b>	Convection	Heatsink	Fan-Cooled	Water-Cooled

### MEASUREMENT CAPABILITY

Spectral Range <sup>a</sup>	0.3 – 2.5 µm	0.3 – 2.5 µm	0.3 – 2.5 µm	0.3 – 2.5 µm
Noise Equivalent Power <sup>b</sup>	15 mW	15 mW	15 mW	15 mW
Rise Time (nominal) <sup>c</sup>	4 sec	4 sec	4 sec	4 sec
Sensitivity (typ into 100 kΩ load) <sup>d</sup>	0.04 mV/W	0.04 mV/W	0.04 mV/W	0.04 mV/W
Calibration Uncertainty <sup>e</sup>	±2.5 %	±2.5 %	±2.5 %	±2.5 %
Repeatability	±0.5 %	±0.5 %	±0.5 %	±0.5 %
Energy Mode				
Sensitivity	0.028 mV/J	0.028 mV/J	0.015 mV/J	0.015 mV/J
Maximum Measurable Energy <sup>f</sup>	200 J	200 J	200 J	200 J
Noise Equivalent Energy <sup>b</sup>	0.25 J	0.25 J	0.25 J	0.25 J
Minimum Repetition Period	11.1 sec	11.1 sec	12 sec	12 sec
Maximum Pulse Width	433 ms	433 ms	430 ms	430 ms
Accuracy with energy calibration option	±5 %	±5 %	±5 %	±5 %

### DAMAGE THRESHOLDS

Maximum Average Power Density <sup>h</sup>	700 W/cm <sup>2</sup>	700 W/cm <sup>2</sup>	700 W/cm <sup>2</sup>	700 W/cm <sup>2</sup>
Pulsed Laser Damage Thresholds	Max Energy Density		Peak Power Density	
1064 nm, 360 µs, 5 Hz	40 J/cm <sup>2</sup>		111 kW/cm <sup>2</sup>	
1064 nm, 7 ns, 10 Hz	6 J/cm <sup>2</sup>		860 MW/cm <sup>2</sup>	
532 nm, 7 ns, 10 Hz	4 J/cm <sup>2</sup>		570 MW/cm <sup>2</sup>	
266 nm, 7 ns, 10 Hz	1 J/cm <sup>2</sup>		143 MW/cm <sup>2</sup>	

### PHYSICAL CHARACTERISTICS

Effective Aperture	55 mm Ø	55 mm Ø	55 mm Ø	55 mm Ø
Absorber (Volume Absorber)	VR	VR	VR	VR
Dimensions	89H x 89W x 32D mm	89H x 89W x 106D mm	89H x 89W x 116D mm	89H x 89W x 44D mm
Weight (head only)	0.62 kg	0.93 kg	1.41 kg	0.84 kg

### ORDERING INFORMATION

Full Product Name	UP55N-50S-VR	UP55N-100H-VR	UP55N-150F-VR	UP55M-200W-VR
Product Number (Including stand)	201296	201934	201856	201292

a. Adjustment multipliers for wavelengths under 300 nm are not traceable.  
 b. Nominal value, actual value depends on electrical noise in the measurement system.  
 c. With Gentec-EO MAESTRO, UNO, P-LINK, TUNER and S-LINK-2 monitors.  
 d. Maximum output voltage = sensitivity x maximum power.  
 e. Including linearity with power.

f. For 360 µs pulses. Higher pulse energy possible when customized for long pulses (ms), less for short pulses (ns).  
 g. Minimum cooling flow 1 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube.  
 Contact Gentec-EO for clean deionized water cooling module option.  
 h. At 1064 nm, 10 W CW.

Specifications are subject to change without notice

[www.gmp.ch](http://www.gmp.ch)

GMP SA Main office: Avenue des Baumettes 17 CH -1020 Renens Tél. 021 633 21 21 Fax. 021 633 21 29 info@gmp.ch  
 GMP SA Büro Zürich: Dübendorfstrasse 11a CH-8117 Fällanden Tel. 044 825 34 00 Fax. 044 825 34 01 info@gmp.ch