# Nanosecond, high average power 1064nm lasers

### Features & benefits

**High pulse energy** As high as 30µJ

High average power To 400mW

**Excellent beam quality** Gaussian, TEM00, M<sup>2</sup>≤1.3

Efficient, air cooled Typically dissipates <10W from laser head and consumes <20W

#### Long life

High reliability pump diode, specialty optics, and sealed package contribute to lifetimes expected to exceed 5k hours (consult factory for details)

#### Licensed Technology

Exclusive license on passively Q-switched microchip laser: US Patent 5394413

### **Optional features**

#### User control of repetition rate for varying average power

- From 100% to a fraction of free running frequency
- RS232 (≤100ms delay) or analog input

#### Manual controls for CDRH compliance

# **1064nm Passively Q-Switched Nd:YAG lasers:** hundreds of mW average power, adjustable

Identical in package size to picosecond microchip lasers, longer pulsed passively Q-switched (PQS) nanosecond lasers provide far Incorporating more power. а YAG proprietary Nd: engine pumped by a high power diode, these compact lasers generate



hundreds of milliWatts at 1064nm. The SNP-400P produces 400mW; the SNP-30E emits over 30µJ per pulse; the SNP-7PW optimizes between pulse energy and average power, delivering 21µJ per pulse and 350mW. The SNP series, which comes standard with a MLC-03A-xR0 controller, emits pulses at its free running PQS repetition rate; when used with the optional MLC-03A-DR2 controller, these laser can emit at frequencies from 100% down to a fraction of their free running speeds (actual fraction depends on the application and laser model selected and must be determined in consultation with factory). This optional control allows the user to adjust the average power, as is often required in material processing applications.

# **MicroChip SNP Lasers**

Model	SNP-30E*	SNP-7PW	SNP-400P*
Energy/Pulse (µJ)	33	21	15
Repetition rate (kHz)	5	17	28
Peak Power (kW)	6	4	2
Average Power (mW)	180	350	420
Pulse Width (ps)	7000	5500	10000

\*Preliminary specifications. Please contact Teem Photonics for availability | Typical values

## **Applications**

- Material processing
  - o Marking
- o Graphitization
- Biophotonics
- Instrumentation



**teem**photonics™